PREDICTED ENERGY ASSESSMENT




Plot 26, Land off Hawks Road, Dwelling type: House, Semi-Detached

Welton, Date of assessment: 19/07/2022 Lincoln, Produced by: Jake Eaton LN2 3BS Total floor area: 81.47 m²

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.


The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO₂) emissions.

Energy Efficiency Rating



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

Environmental Impact (CO₂) Rating



The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO₂) emissions. The higher the rating the less impact it has on the environment.

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Property Reference	LN2 3BS Plot 26				Issued on Date	19/07/2022
Assessment Reference	001 Prop Type Ref Greenwich (Type B)					
Property	Plot 26, Land off Hawk	s Road, Welton,	Lincoln, LN2 3BS			
SAP Rating		84 B	DER	17.48	TER	18.48
Environmental		87 B	% DER <ter< td=""><td></td><td>5.42</td><td></td></ter<>		5.42	
CO ₂ Emissions (t/year)		1.26	DFEE	44.86	TFEE	52.67
General Requirements	Compliance	Pass	% DFEE <tfee< td=""><td></td><td>14.83</td><td></td></tfee<>		14.83	
Assessor Details M	r. Jake Eaton, Jake Eator	n, Tel: 014002834	171, jake@aerate	ch.co.uk	Assessor ID	P711-0001
Client						
UMARY FOR INPUT D	ATA FOR New Build (As	Designed)				
riterion 1 – Achieving	the TER and TFEE rate					
a TER and DER						
Fuel for main heatir	ng	Mains g	as			
Fuel factor		1.00 (ma	ains gas)			
Target Carbon Dioxi	18.48			kgCO₂/m²		
Dwelling Carbon Did	17.48			kgCO ₂ /m ²	Pass	
		-1.00 (-5	5.4%)		kgCO₂/m²	
b TFEE and DFEE						
Target Fabric Energy Efficiency (TFEE)		52.67			kWh/m²/yr	
Dwelling Fabric Ene	rgy Efficiency (DFEE)	44.86			kWh/m²/yr	
		-7.8 (-14	.8%)		kWh/m²/yr	Pass
riterion 2 – Limits on	-					
Limiting Fabric Stan	dards					
2 Fabric U-values						
Element	A	verage	F	lighest		
External wall	0.	19 (max. 0.30)	C).19 (max. 0.70)	Pass
Party wall	0.	00 (max. 0.20)		-		Pass
Floor	0.	0.14 (max. 0.25)).14 (max. 0.70)	Pass
Roof	0.	0.11 (max. 0.20)).12 (max. 0.35)	Pass
Openings	1.	1.40 (max. 2.00)		L.40 (max. 3.30)	Pass
2a Thermal bridging	3					
Thermal bridging	g calculated from linear	thermal transmit	tances for each ju	ınction		
3 Air permeability						
Air permeability at 50 pascals		7.00 (de	sign value)		m³/(h.m²) @ 50 Pa	
Air permeability	at 30 pascais	7.00 (0.0	- 0 /		, , , ,	

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



4 Heating efficiency

Regs Region: England Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r19

BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Main heating system	Boiler system with radiators or underfloor - Mains gas Data from database Vaillant ecoFIT sustain 835 VUW 356/6-3 (H-GB) Combi boiler Efficiency: 89.3% SEDBUK2009 Minimum: 88.0%	Pass
Secondary heating system	None	
5 Cylinder insulation		
Hot water storage	No cylinder	
<u>6 Controls</u>		
Space heating controls	Programmer, room thermostat and TRVs	Pass
Hot water controls	No cylinder	i
Boiler interlock	Yes	Pass
7 Low energy lights		
Percentage of fixed lights with low-energy fittings	100 %	
Minimum	75 %	Pass
8 Mechanical ventilation		
Not applicable		
Criterion 3 – Limiting the effects of heat gains in sur	mmer	
9 Summertime temperature		
Overheating risk (East Pennines)	Slight	Pass
Based on:		
Overshading	Average	
Windows facing North	4.54 m², No overhang	
Windows facing South	6.91 m², No overhang	
Windows facing West	1.45 m², No overhang	=
Air change rate	2.50 ach	_
Blinds/curtains	Light-coloured curtain or roller blind, closed 50% of daylight hours	
Criterion 4 – Building performance consistent with		
Party Walls		
Туре	U-value	
Filled Cavity with Edge Sealing	0.00 W/m²K	Pass
Air permeability and pressure testing		
3 Air permeability		
Air permeability at 50 pascals	7.00 (design value) m ³ /(h.m ²) @ 50 Pa	
Maximum	10.0 m ³ /(h.m ²) @ 50 Pa	Pass
10 Key features		
Party wall U-value	0.00 W/m²K	
Roof U-value	0.11 W/m²K	
Roof U-value	0.12 W/m²K	

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



Regs Region: England Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r19