### PREDICTED ENERGY ASSESSMENT



Plot 3, Land off Hawks Road, Dwelling type: House, Detached

Welton, Date of assessment: 19/07/2022 Lincoln, Produced by: Jake Eaton LN2 3BS Total floor area: 133.94 m²


This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.

# Very energy efficient - lower running costs (92 plus) A (81-91) B (69-80) C (55-68) D (39-54) E (21-38) F (1-20) Not energy efficient - higher running costs Even Lored EU Directive

The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

### Environmental Impact (CO<sub>2</sub>) Rating



The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



**England** 

2002/91/EC

# **BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)**



Property Reference LN2 3BS Plot 3				Issued on Date	19/07/2022
Assessment 001		Pro	op Type Ref	Regent (Type H)	
Reference					
Property Plot 3, Land off Hawks Road, Welton, Lincoln, LN2 3BS					
SAP Rating	85 B	DER	15.94	TER	16.37
Environmental	86 B	% DER <ter< td=""><td></td><td>2.64</td><td></td></ter<>		2.64	
CO <sub>2</sub> Emissions (t/year)	1.92	DFEE	48.03	TFEE	56.55
General Requirements Compliance	Pass	% DFEE <tfee< td=""><td></td><td>15.07</td><td></td></tfee<>		15.07	
Assessor Details Mr. Jake Eaton, Jake Eaton	n, Tel: 014002834	71, jake@aeratech	h.co.uk	Assessor ID	P711-0001
Client					
SUMARY FOR INPUT DATA FOR New Build (As	Designed)				
Criterion 1 – Achieving the TER and TFEE rate					
1a TER and DER					
Fuel for main heating	Mains ga	IS .			
Fuel factor	1.00 (ma	ins gas)			
Target Carbon Dioxide Emission Rate (TER)	16.37			kgCO₂/m²	
Dwelling Carbon Dioxide Emission Rate (DEF	15.94			kgCO <sub>2</sub> /m <sup>2</sup>	Pass
	-0.43 (-2	.6%)		kgCO₂/m²	
1b TFEE and DFEE					
Target Fabric Energy Efficiency (TFEE)	56.55			kWh/m²/yr	
Dwelling Fabric Energy Efficiency (DFEE)	48.03	00()	,	kWh/m²/yr	
Colonia 2 Units and also for thillies	-8.5 (-15	.0%)		kWh/m²/yr	Pass
Criterion 2 – Limits on design flexibility					
Limiting Fabric Standards					
2 Fabric U-values					
	verage		ghest	1)	Dono
	19 (max. 0.30) 00 (max. 0.20)	U -	19 (max. 0.70	))	Pass
	14 (max. 0.25)		14 (max. 0.70	1)	Pass
	11 (max. 0.20)		14 (max. 0.76 11 (max. 0.35	•	Pass
	40 (max. 2.00)		40 (max. 3.30	•	Pass
2a Thermal bridging	( = ====		,	,	
Thermal bridging calculated from linear	thermal transmitt	ances for each jun	nction		
3 Air permeability	7	•			
Air permeability at 50 pascals	7.00 (des	7.00 (design value) m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa			a
Maximum	10.0	<u> </u>		m³/(h.m²) @ 50 Pa	
				•	
Limiting System Efficiencies					

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



Regs Region: England Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r19

# **BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)**



Main heating system	Boiler system with radiators or underfloor - Mains gas	Pass	
	Data from database		
	Vaillant ecoFIT sustain 615 VU 156/6-3 (H-GB)		
	Efficiency: 89.8% SEDBUK2009		
	Minimum: 88.0%		
Secondary heating system	None		
5 Cylinder insulation			
Hot water storage	Measured cylinder loss: 1.31 kWh/day	Pass	
G	Permitted by DBSCG 2.10		
Primary pipework insulated	Yes	Pass	
<u>6 Controls</u>			
Space heating controls	Time and temperature zone control	Pass	
Hot water controls	Cylinderstat	Pass	
	Independent timer for DHW	Pass	
Boiler interlock	Yes	Pass	
7 Low energy lights			
Percentage of fixed lights with low-energy	100 %		
fittings			
Minimum	75 %	Pass	
8 Mechanical ventilation			
Not applicable			
Criterion 3 – Limiting the effects of heat gains in su	mmer		
9 Summertime temperature			
Overheating risk (East Pennines)	Slight	Pass	
Based on:			
Overshading	Average		
Windows facing East	12.94 m², No overhang		
Windows facing West	9.04 m <sup>2</sup> , No overhang		
Air change rate	2.50 ach		
Blinds/curtains	Light-coloured curtain or roller blind, closed 50% of daylight		
	hours		
Criterion 4 – Building performance consistent with	DER and DFEE rate		
Party Walls			
Туре	U-value		
	W/m²K	Pass	
Air permeability and pressure testing			
3 Air permeability			
Air permeability at 50 pascals	7.00 (design value) m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa		
Maximum	10.0 m <sup>3</sup> /(h.m <sup>2</sup> ) @ 50 Pa		

This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



# **BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)**



### 10 Key features

Party wall U-value Roof U-value Thermal bridging y-value

0.00	W/m²K
0.11	W/m²K
0.032	W/m²K



This report has not been submitted through the Elmhurst Energy members' portal, therefore results are subject to change when the dwelling is completed.



Regs Region: England Elmhurst Energy Systems SAP2012 Calculator (Design System) version 4.14r19